



BSU364EU

OBMINI FA MSU EU

- OB MINI medical suction unit
- Maintenance-free piston pump
- Nominal suction power: 850 mbar (85 kPa) $\pm 10\%$
- Nominal suction flow: 25 LPM at free air speed $\pm 10\%$
- Maximum operating time (free-cycle): 60 minutes $\pm 10\%$
- Inorganic solid-type lithium polymer battery
- Degree of protection against infiltration of liquids and solids: IP43
- Functioning/charge: 11÷30 Vdc
- Autoclavable collection jar OB-J FA 1000 ml with overflow valve and protective filter inserted directly in the lid, autoclavable max 30 cycles
- Possibility of viewing the battery charge status without having to switch on the device.
- The OB MINI suction unit is equipped with an internal microprocessor control that allows the storage of device construction and operating data
- A special function alerts the user of the need for a scheduled device maintenance
- Equipped with an external mains-voltage EU power supply with 2-pole plug (mains power supply between 100 and 240 Vac)
- Dimensions: 290x240x95 mm
- Weight: 1.8 kg complete with accessories
- In compliance with all applicable regulations, Directive 93/42/EEC and the main reference standards

User manual available on the [eIFU](#) webpage

For further information and/or technical data related to the product, please refer to the Oscar Boscarol Company.