BSU158ST

OB2012 FA MSU WB EU

- OB2012 medical suction unit equipped with:
  - Autoclavable collection jar OB-J FA 1000 ml with overflow valve and protective filter inserted directly in the lid, autoclavable max 30 cycles
  - OB WB charging bracket (in accordance with EN 1789)
  - external EU mains-voltage power supply with 2-pole plug (mains power supply between 100 and 240 Vac)
- Nominal suction power: 800 mbar (80 kPa) ±10%
- Nominal suction flow: 30 LPM at free air speed ±10%
- Maximum operating time (free-cycle): 60 minutes ±10%
- Degree of protection against infiltration of liquids and solids: IP34d
- Functioning/charge: 12÷15 Vdc
- Maintenance-free piston pump
- Sealed lead-acid battery
- The suction unit can be equipped with recharging cable complete with cigarette lighter plug and 2-pole connector
- Dimensions: 350x240x120 mm
- Weight: 4.6 kg complete with accessories, without support bracket
- Class IIa medical device in compliance with Regulation (EU) 2017/745 (MDR), all applicable regulations and main reference standards

User manual available on the eIFU webpage

For further information and/or technical data related to the product, please refer to the Oscar Boscarol Company.

OSCAR BOSCAROL S.r.l.
Via Enzo Ferrari, 29 - 39100 Bolzano BZ Italy
VAT Number e Fisc. Code 01458460217
Ph. +39 0471932893 Fax. +39 04711880333
info@boscarol.it - www.boscarol.it